

RIMS

Product group	Rims
Item number	32013619
Valid rim size	17.00 - 25 / 1.7
Rim connection	12/371/425
Bolt hole design	A3
Offset (mm)	+27
Rim colour	Anthrazit
Brand	Moveero

Technical Informations

Load capacity of rim 1 [kg]	5330
Speed Rims 1 [km/h]	12
Load capacity of rim 2 [kg]	2660
Speed Rims 2 [km/h]	38
Maximum speed [km/h].	38
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	169.00
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	three-part
Rim material	steel

RAL	RAL7016
Cavity Sealed	No
Rim design industry	Standard
Rim flange height [inch]	1.7
Disc thickness [mm]	13
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	12
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	371
Bolt hole circle diameter [mm]	425
Valve seat	External Valve
Valve hole diameter [mm]	20.5
Preassembled valve	No