

RIMS

Product group	Rims
Item number	32013639
Valid rim size	DW 18 L x 38
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+130
Rim colour	Silver
Brand	GKN





Technical Informations		
Load capacity of rim 1 [kg]	5800	
Speed Rims 1 [km/h]	40	
Load capacity of rim 2 [kg]	5800	
Speed Rims 2 [km/h]	50	
Maximum speed [km/h].	50	
Nettogewicht [kg] (gültig)	138,20	
Hump	kein Hump	
Single / multi-part	einteilig	
Rim material	steel	
RAL	RAL9006	
Cavity Sealed	No	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Disc thickness [mm]	15
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No