

## RIMS

|                  |              |
|------------------|--------------|
| Product group    | Rims         |
| Item number      | 32013643     |
| Valid rim size   | TW 20 B x 38 |
| Rim connection   | 10/281/335   |
| Bolt hole design | A3           |
| Offset (mm)      | -50          |
| Rim colour       | Silver       |
| Brand            | Moveero      |



## Technical Informations

|                             |            |
|-----------------------------|------------|
| Load capacity of rim 1 [kg] | 7500       |
| Speed Rims 1 [km/h]         | 40         |
| Load capacity of rim 2 [kg] | 7000       |
| Speed Rims 2 [km/h]         | 50         |
| Maximum speed [km/h].       | 50         |
| Type of drive               | Towed axle |
| Nettogewicht [kg] (gültig)  | 160,00     |
| Hump                        | kein Hump  |
| Single / multi-part         | einteilig  |
| Rim material                | steel      |
| RAL                         | RAL9006    |

---

|                                |                  |
|--------------------------------|------------------|
| Cavity Sealed                  | No               |
| Disc thickness [mm]            | 15               |
| Knurling                       | without knurling |
| Verschweißung beidseitig       | No               |
| Ventilation holes              | No               |
| Rim centering                  | BC               |
| Number of bolt holes           | 10               |
| Bolt hole design EUWA          | B22 ES 36        |
| Bolt hole diameter [mm]        | 27               |
| Countersinking                 | Sphere           |
| Spherical countersink [mm].    | R18              |
| hub hole diameter [mm].        | 281              |
| Bolt hole circle diameter [mm] | 335              |
| Valve seat                     | External Valve   |
| Valve hole diameter [mm]       | 15.7             |
| Preassembled valve             | No               |
| TPMS-kompatibles Ventil        | No               |