

Verschweißung beidseitig

No

RIMS

Product group	Rims
Item number	32013680
Valid rim size	DW 10 x 46
Rim connection	10/281/335
Bolt hole design	В3
Offset (mm)	+70
Rim colour	Red
Brand	GKN





Technical Informations		
Load capacity of rim 1 [kg]	3150	
Speed Rims 1 [km/h]	65	
Maximum speed [km/h].	65	
Nettogewicht [kg] (gültig)	149,00	
Hump	kein Hump	
Single / multi-part	einteilig	
Rim material	steel	
RAL	RAL3000	
Cavity Sealed	No	
Disc thickness [mm]	11	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Preassembled valve	No