

## RIMS

Product group	Rims
Item number	32013702
Valid rim size	DW 12 x 50
Rim connection	12/351/400
Bolt hole design	B3
Offset (mm)	+35
Rim colour	Silver
Brand	GKN



## Technical Informations

Load capacity of rim 1 [kg]	5900
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5700
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	50
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	206.30
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel

---

<b>RAL</b>	RAL9006
<b>Cavity Sealed</b>	No
<b>Disc thickness [mm]</b>	15
<b>Verschweißung beidseitig</b>	No
<b>Ventilation holes</b>	No
<b>Rim centering</b>	BC
<b>Number of bolt holes</b>	12
<b>Bolt hole design EUWA</b>	B22 DS 36
<b>Bolt hole diameter [mm]</b>	27
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R18
<b>hub hole diameter [mm].</b>	351
<b>Bolt hole circle diameter [mm]</b>	400
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No