Bohnenkamp Moving Professionals

RIMS

| Product group | Rims |
|------------------|--------------|
| Item number | 32016649 |
| Valid rim size | TW 16 L x 42 |
| Rim connection | 10/281/335 |
| Bolt hole design | A3 |
| Rim colour | Silver |
| Brand | GKN |





Technical Informations Load capacity of rim 1 [kg] 5450 Speed Rims 1 [km/h] 40 Load capacity of rim 2 [kg] 5000 Speed Rims 2 [km/h] 65 Maximum speed [km/h]. 65 Nettogewicht [kg] (gültig) 171,00 Hump kein Hump Single / multi-part einteilig **Rim material** steel RAL9006 RAL **Cavity Sealed** No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

| Verschweißung beidseitig | No |
|--------------------------------|----------------|
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 10 |
| Bolt hole design EUWA | B22 ES 36 |
| Bolt hole diameter [mm] | 27 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| hub hole diameter [mm]. | 281 |
| Bolt hole circle diameter [mm] | 335 |
| Valve seat | External Valve |
| Preassembled valve | No |