

RIMS

Product group	Rims
Item number	32100747
Valid rim size	DW 25 B x 26
Rim connection	12/372/425
Bolt hole design	A3
Offset (mm)	-70
Rim colour	Silver
Brand	Levypyoera



Technical Informations

Load capacity of rim 1 [kg]	12117
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	10663
Speed Rims 2 [km/h]	65
Load capacity of rim 3 [kg]	16842
Speed Rims 3 [km/h]	10
Load capacity of rim 4 [kg]	14177
Speed of wheels 4 [km/h].	25
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	100,00

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Forest reinforcement	flange reinforcement 15 x 35 mm
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	12
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	372
Bolt hole circle diameter [mm]	425
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No