Bohnenkamp Moving Professionals

19.09.2024

RIMS

Product group	Rims
Item number	32100749
Valid rim size	DW 23 B x 38
Rim connection	10/281/335
Offset (mm)	-75
Rim colour	Black
Brand	Levypyoera



Technical Informations

Load capacity of rim 1 [kg]	8750
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	188,00
Hump	kein Hump
Valve protection	VS V
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9005
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Forest reinforcement	flange reinforcement Ø19 mm
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	M20
Bolt hole diameter [mm]	24
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.