

RIMS

Product group	Rims
Item number	33060010
Valid rim size	6.00 J x 15 H2
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	+70
Rim colour	Silver
Brand	Jantsa





Technical Informations		
Load capacity of rim 1 [kg]	1600	
Speed Rims 1 [km/h]	50	
Maximum speed [km/h].	50	
Type of drive	Angetriebene & gezogene Achse	
Nettogewicht [kg] (gültig)	10,90	
Hump	H2	
Single / multi-part	einteilig	
Rim material	steel	
RAL	RAL9006	
Cavity Sealed	No	
Verschweißung beidseitig	No	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Ventilation holes	Yes
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No