Bohnenkamp Moving Professionals

22.09.2024

RIMS

Product group	Rims
Item number	33060024
Valid rim size	9.00 x 15.3
Rim connection	5/66.5/112
Bolt hole design	A1
Offset (mm)	+60
Rim colour	Silver
Brand	Jantsa



ijantsa

Technical Informations	
Load capacity of rim 1 [kg]	1900
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2250
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	15,00
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel

Technical Informations

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	66.5
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No