

## **RIMS**

Product group	Rims
Item number	33060027
Valid rim size	9.00 x 15.3
Rim connection	8/190/210
Offset (mm)	-10
Rim colour	Silver
Brand	Jantsa





Technical Informations		
Load capacity of rim 1 [kg]	3550	
Speed Rims 1 [km/h]	25	
Load capacity of rim 2 [kg]	3100	
Speed Rims 2 [km/h]	40	
Maximum speed [km/h].	40	
Nettogewicht [kg] (gültig)	17,00	
Hump	kein Hump	
Valve protection	VS H	
Single / multi-part	einteilig	
Rim material	steel	
RAL	RAL9006	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	11
hub hole diameter [mm].	190
Bolt hole circle diameter [mm]	210
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No