

RIMS

Product group	Rims
Item number	33060032
Valid rim size	8.0 - 15
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Brand	Jantsa





Technical Informations		
Load capacity of rim 1 [kg]	6000	
Speed Rims 1 [km/h]	25	
Maximum speed [km/h].	25	
Type of drive	Angetriebene & gezogene Achse	
Nettogewicht [kg] (gültig)	29,00	
Hump	kein Hump	
Single / multi-part	mehrteilig	
Quantity multi-piece	four-part	
Rim material	steel	
RAL	RAL9006	
Cavity Sealed	No	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rim design industry	Standard
Disc thickness [mm]	14
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No