

RIMS

Product group	Rims
Item number	33060041
Valid rim size	16.00 x 17
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Brand	Jantsa





Technical Informations	
Load capacity of rim 1 [kg]	5200
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4400
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	30,00
Hump	kein Hump
Valve protection	VS V
Single / multi-part	einteilig
Rim material	steel

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



RAL	RAL9006
Cavity Sealed	No
Forest reinforcement	flange reinforcement Ø16 mm
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No