

RIMS

Product group	Rims
Item number	33060060
Valid rim size	6.75 x 17.5
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Brand	Jantsa





Technical Informations	
Load capacity of rim 1 [kg]	4050
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3350
Speed Rims 2 [km/h]	50
Load capacity of rim 3 [kg]	3000
Speed Rims 3 [km/h]	105
Load capacity of rim 4 [kg]	2800
Speed of wheels 4 [km/h].	120
Maximum speed [km/h].	120
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	25,20

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole design EUWA	B18 ES 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
TPMS-kompatibles Ventil	No