Bohnenkamp Moving Professionals

20.09.2024

RIMS

Product group	Rims
Item number	33060063
Valid rim size	6.75 x 17.5
Rim connection	8/221/275
Bolt hole design	B2
Offset (mm)	+118
Half centre distance (HMA) [mm]	130
Rim colour	Silver
Brand	Jantsa





Load capacity of rim 1 [kg] 4050 Speed Rims 1 [km/h] 25 Load capacity of rim 2 [kg] 3000 Speed Rims 2 [km/h] 100 Maximum speed [km/h]. 100 Type of drive Angetriebene & gezogene Achse Nettogewicht [kg] (gültig) 24,00 Hump kein Hump Single / multi-part einteilig **Rim material** steel RAL9006 RAL

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Technical Informations

Bohnenkamp Moving Professionals

Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No