Bohnenkamp Moving Professionals

20.09.2024

RIMS

Product group	Rims
Item number	33060068
Valid rim size	6.75 x 17.5
Rim connection	10/176/225
Bolt hole design	A3
Offset (mm)	-40
Rim colour	Silver
Brand	Jantsa





Load capacity of rim 1 [kg] 3000 Speed Rims 1 [km/h] 100 Maximum speed [km/h]. 100 Type of drive Angetriebene & gezogene Achse Nettogewicht [kg] (gültig) 26,50 Hump kein Hump Single / multi-part einteilig **Rim material** steel RAL RAL9006 **Cavity Sealed** No Verschweißung beidseitig No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Technical Informations

Bohnenkamp Moving Professionals

Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No