

RIMS

Product group	Rims
Item number	33060073
Valid rim size	13.00 x 17
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Brand	Jantsa



Allgemeine Produktabbildung. Artikel kann abweichen



Technical Informations

Load capacity of rim 1 [kg]	4150
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	26,00
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No