Bohnenkamp Moving Professionals

14.03.2025

RIMS

| Product group | Rims |
|------------------|------------|
| Item number | 33060076 |
| Valid rim size | 13.00 × 17 |
| Rim connection | 6/161/205 |
| Bolt hole design | A2 |
| Rim colour | Silver |
| Brand | Jantsa |





Technical Informations Load capacity of rim 1 [kg] 4000 Speed Rims 1 [km/h] 25 Load capacity of rim 2 [kg] 3400 Speed Rims 2 [km/h] 40 Maximum speed [km/h]. 40 Nettogewicht [kg] (gültig) 25,10 Hump kein Hump Valve protection VSH Single / multi-part einteilig **Rim material** steel RAL9006 RAL

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

| Cavity Sealed | No |
|--------------------------------|----------------|
| Verschweißung beidseitig | No |
| Number of drain holes | 2 |
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 6 |
| Bolt hole design EUWA | B18 ES 32 |
| Bolt hole diameter [mm] | 21.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |
| hub hole diameter [mm]. | 161 |
| Bolt hole circle diameter [mm] | 205 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |