# Bohnenkamp Moving Professionals

22.09.2024

### RIMS

Product group	Rims
Item number	33060110
Valid rim size	14.00 x 17.5
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Brand	Jantsa





#### Load capacity of rim 1 [kg] 6150 Speed Rims 1 [km/h] 25 Load capacity of rim 2 [kg] 5200 Speed Rims 2 [km/h] 40 Maximum speed [km/h]. 40 Type of drive Angetriebene & gezogene Achse Nettogewicht [kg] (gültig) 36,50 Hump kein Hump Valve protection VS H Single / multi-part einteilig **Rim material** steel

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

#### **Technical Informations**

## Bohnenkamp Moving Professionals

RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No