

## **RIMS**

Product group	Rims
Item number	33060117
Valid rim size	13.00 X 17
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	-54
Rim colour	Silver
Brand	Jantsa





Technical Informations		
Load capacity of rim 1 [kg]	3800	
Speed Rims 1 [km/h]	40	
Load capacity of rim 2 [kg]	2800	
Speed Rims 2 [km/h]	65	
Maximum speed [km/h].	65	
Type of drive	Angetriebene & gezogene Achse	
Nettogewicht [kg] (gültig)	26,00	
Hump	kein Hump	
Valve protection	VSH	
Single / multi-part	einteilig	
Rim material	steel	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole design EUWA	B18 DS 32
Bolt hole diameter [mm]	21.5
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No