## Bohnenkamp Moving Professionals

22.09.2024

## RIMS

Product group	Rims
Item number	33060118
Valid rim size	9.00 x 15.3
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	+40
Rim colour	Anthrazit
Brand	Jantsa





Technical Informations	
Load capacity of rim 1 [kg]	3250
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2750
Speed Rims 2 [km/h]	40
Load capacity of rim 3 [kg]	3650
Speed Rims 3 [km/h]	15
Load capacity of rim 4 [kg]	3050
Speed of wheels 4 [km/h].	30
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	15,00

Technical Informations

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL7016
Cavity Sealed	No
Disc thickness [mm]	8
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole design EUWA	B18 ES 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.