

RIMS

Product group	Rims
Item number	33060151
Valid rim size	7.5 - 20
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+143
Half centre distance (HMA) [mm]	155
Rim colour	Black
Brand	Jantsa



Technical Informations

Load capacity of rim 1 [kg]	6500
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3400
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	100
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	47,10
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	two-part
Rim material	steel

RAL	RAL9005
Cavity Sealed	No
Rim design industry	Standard
Disc thickness [mm]	12
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	Internal Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No