

RIMS

Product group	Rims
1 Toutiet group	TAIIIS
Item number	33060151
Valid rim size	7.5 - 20
Rim connection	10/281/335
Bolt hole design	В3
Offset (mm)	+143
Half centre distance (HMA) [mm]	155
Rim colour	Black
Brand	Jantsa





Technical Informations	
Load capacity of rim 1 [kg]	6500
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3400
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	100
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	47,10
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	two-part
Rim material	steel

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



RAL	RAL9005
Cavity Sealed	No
Rim design industry	Standard
Disc thickness [mm]	12
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	Internal Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No