

RIMS

| | |
|---------------------------------|------------|
| Product group | Rims |
| Item number | 33060156 |
| Valid rim size | 8.0 - 20 |
| Rim connection | 10/281/335 |
| Bolt hole design | B3 |
| Offset (mm) | +153 |
| Half centre distance (HMA) [mm] | 165 |
| Rim colour | Black |
| Brand | Jantasa |



Technical Informations

| | |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 7100 |
| Speed Rims 1 [km/h] | 25 |
| Maximum speed [km/h]. | 25 |
| Type of drive | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig) | 48,00 |
| Hump | kein Hump |
| Single / multi-part | mehrteilig |
| Quantity multi-piece | two-part |
| Rim material | steel |
| RAL | RAL9005 |
| Cavity Sealed | No |

| | |
|--------------------------------|------------------|
| Rim design industry | Standard |
| Disc thickness [mm] | 12 |
| Knurling | without knurling |
| Verschweißung beidseitig | No |
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 10 |
| Bolt hole design EUWA | B22 DS 36 |
| Bolt hole diameter [mm] | 27 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| hub hole diameter [mm]. | 281 |
| Bolt hole circle diameter [mm] | 335 |
| Valve seat | Internal Valve |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |