

RIMS

Product group	Rims
Item number	33060168
Valid rim size	13 x 20
Rim connection	8/221/275
Offset (mm)	-27.5
Brand	Jantsa





Technical Informations		
Load capacity of rim 1 [kg]	4750	
Speed Rims 1 [km/h]	25	
Load capacity of rim 2 [kg]	4000	
Speed Rims 2 [km/h]	40	
Maximum speed [km/h].	40	
Type of drive	Angetriebene & gezogene Achse	
Nettogewicht [kg] (gültig)	32,50	
Hump	kein Hump	
Valve protection	VSH	
Single / multi-part	einteilig	
Rim material	steel	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rim colour (manufacturer's designation)	Komatsu - grey
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	НВ
Number of bolt holes	8
Bolt hole diameter [mm]	17
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No