

RIMS

Product group	Rims
Item number	33060212
Valid rim size	8.25 x 22.5
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	-159
Rim colour	Black
Brand	Jantsa





Technical Informations	
Load capacity of rim 1 [kg]	5100
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4300
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Nettogewicht [kg] (gültig)	30,00
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9005

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Disc thickness [mm]	12
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No