

RIMS

| | |
|------------------|--------------|
| Product group | Rims |
| Item number | 33060253 |
| Valid rim size | 11.75 x 22.5 |
| Rim connection | 6/161/205 |
| Bolt hole design | B2 |
| Offset (mm) | -40 |
| Rim colour | Silver |
| Brand | Jantsa |



Technical Informations

| | |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 5600 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 4700 |
| Speed Rims 2 [km/h] | 80 |
| Maximum speed [km/h]. | 80 |
| Type of drive | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig) | 52,00 |
| Hump | kein Hump |
| Valve protection | VS H |
| Single / multi-part | einteilig |
| Rim material | steel |

| | |
|---------------------------------------|----------------|
| RAL | RAL9006 |
| Cavity Sealed | No |
| Verschweißung beidseitig | No |
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 6 |
| Bolt hole diameter [mm] | 21.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |
| hub hole diameter [mm]. | 161 |
| Bolt hole circle diameter [mm] | 205 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |