Bohnenkamp Moving Professionals

20.09.2024

RIMS

Product group	Rims
Item number	33060268
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	M22
Offset (mm)	+120
Half centre distance (HMA) [mm]	134
Rim colour	Silver
Brand	Jantsa



ijantsa

Technical Informations

Load capacity of rim 1 [kg]	4500
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	52,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	14

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	НВ
Number of bolt holes	10
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No