

## **RIMS**

Product group	Rims
Item number	33060278
Valid rim size	11.75 X 22.5
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-85
Rim colour	Black
Brand	Jantsa





Technical Informations	
Load capacity of rim 1 [kg]	7500
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	5000
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	80
Nettogewicht [kg] (gültig)	47,00
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9011

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	Yes
Rim centering	BC
Number of bolt holes	10
Bolt hole diameter [mm]	27
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No