Bohnenkamp Moving Professionals

21.09.2024

RIMS

Product group	Rims
Item number	33060313
Valid rim size	14.00 x 22.5
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	+30
Rim colour	Silver
Brand	Jantsa





Technical Informations Load capacity of rim 1 [kg] 5150 Speed Rims 1 [km/h] 100 Maximum speed [km/h]. 100 Type of drive Angetriebene & gezogene Achse Nettogewicht [kg] (gültig) 53,00 Hump kein Hump Single / multi-part einteilig **Rim material** steel RAL RAL9006 **Cavity Sealed** No 12 Disc thickness [mm]

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No