

RIMS

Product group Rims Item number 33060359 Valid rim size AG 16.00 x 22.5 H2 Rim connection 10/281/335 Bolt hole design B3 Offset (mm) -85 Rim colour Silver Brand Jantsa		
Valid rim size Rim connection 10/281/335 Bolt hole design B3 Offset (mm) -85 Rim colour Silver	Product group	Rims
Rim connection 10/281/335 Bolt hole design B3 Offset (mm) -85 Rim colour Silver	Item number	33060359
Bolt hole design B3 Offset (mm) -85 Rim colour Silver	Valid rim size	AG 16.00 x 22.5 H2
Offset (mm) -85 Rim colour Silver	Rim connection	10/281/335
Rim colour Silver	Bolt hole design	В3
	Offset (mm)	-85
Brand Jantsa	Rim colour	Silver
	Brand	Jantsa





Technical Informations		
Load capacity of rim 1 [kg]	7250	
Speed Rims 1 [km/h]	40	
Load capacity of rim 2 [kg]	5300	
Speed Rims 2 [km/h]	65	
Maximum speed [km/h].	65	
Nettogewicht [kg] (gültig)	50,00	
Hump	H2	
Valve protection	VS H	
Single / multi-part	einteilig	
Rim material	steel	
RAL	RAL9006	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No