

## **RIMS**

Product group Rims  Item number 33060363  Valid rim size AG 16.00 x 22.5 H2
Valid rim size AG 16.00 x 22.5 H2
Rim connection 8/221/275
Bolt hole design B3
Offset (mm) -33
Rim colour Silver
Brand Jantsa





Technical Informations		
Load capacity of rim 1 [kg]	6100	
Speed Rims 1 [km/h]	40	
Load capacity of rim 2 [kg]	4500	
Speed Rims 2 [km/h]	65	
Maximum speed [km/h].	65	
Nettogewicht [kg] (gültig)	50,00	
Hump	H2	
Valve protection	VS H	
Single / multi-part	einteilig	
Rim material	steel	
RAL	RAL9006	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No