

RIMS

Product group	Rims
Item number	33060372
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Red
Brand	Jantsa



Technical Informations		
Load capacity of rim 1 [kg]	7300	
Speed Rims 1 [km/h]	40	
Load capacity of rim 2 [kg]	5400	
Speed Rims 2 [km/h]	65	
Load capacity of rim 3 [kg]	8850	
Speed Rims 3 [km/h]	25	
Maximum speed [km/h].	65	
Nettogewicht [kg] (gültig)	63,50	
Hump	H2	
Valve protection	VS H	
Single / multi-part	einteilig	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rim material	steel
RAL	RAL3000
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole diameter [mm]	27
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No