

RIMS

Product group	Rims
Item number	33060412
Valid rim size	AG 20.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	M22
Offset (mm)	-50
Rim colour	Silver
Brand	Jantsa





Technical Informations	
Load capacity of rim 1 [kg]	5100
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	58,00
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	НВ
Number of bolt holes	10
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No