

## **RIMS**

Product group	Rims
Item number	33060451
Valid rim size	AG 24.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-60
Rim colour	Yellow
Brand	Jantsa





Technical Informations	
Load capacity of rim 1 [kg]	8150
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Nettogewicht [kg] (gültig)	80,00
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL1004

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Forest reinforcement	flange reinforcement Ø16 mm
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No