

RIMS

| Product group | Rims |
|------------------|--------------------|
| Item number | 33060456 |
| Valid rim size | AG 24.00 x 22.5 H2 |
| Rim connection | 8/221/275 |
| Bolt hole design | A2 |
| Offset (mm) | -50 |
| Rim colour | Silver |
| Brand | Jantsa |





| Technical Informations | |
|-----------------------------|------------|
| Load capacity of rim 1 [kg] | 9200 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 6800 |
| Speed Rims 2 [km/h] | 65 |
| Maximum speed [km/h]. | 65 |
| Type of drive | Towed axle |
| Nettogewicht [kg] (gültig) | 79,00 |
| Hump | H2 |
| Valve protection | VS H |
| Single / multi-part | einteilig |
| Rim material | steel |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



| RAL | RAL9006 |
|--------------------------------|----------------|
| Cavity Sealed | No |
| Verschweißung beidseitig | No |
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 8 |
| Bolt hole diameter [mm] | 21.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |
| hub hole diameter [mm]. | 221 |
| Bolt hole circle diameter [mm] | 275 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |