

RIMS

| | |
|------------------|--------------------|
| Product group | Rims |
| Item number | 33060559 |
| Valid rim size | AG 20.00 x 26.5 H2 |
| Rim connection | 10/281/335 |
| Bolt hole design | B3 |
| Rim colour | Silver |
| Brand | Jantsa |



Technical Informations

| | |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 10200 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 7500 |
| Speed Rims 2 [km/h] | 65 |
| Load capacity of rim 3 [kg] | 11850 |
| Speed Rims 3 [km/h] | 25 |
| Load capacity of rim 4 [kg] | 6650 |
| Speed of wheels 4 [km/h]. | 70 |
| Maximum speed [km/h]. | 70 |
| Type of drive | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig) | 85,00 |

| | |
|---------------------------------------|----------------|
| Hump | H2 |
| Valve protection | VS H |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Verschweißung beidseitig | No |
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 10 |
| Bolt hole design EUWA | B22 DS 36 |
| Bolt hole diameter [mm] | 27 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| hub hole diameter [mm]. | 281 |
| Bolt hole circle diameter [mm] | 335 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |