

## **RIMS**

Product group	Rims
Item number	33060573
Valid rim size	AG 24.00 x 26.5 H2
Rim connection	12/372/425
Bolt hole design	A3
Offset (mm)	-5
Rim colour	Yellow
Brand	Jantsa





Technical Informations	
Load capacity of rim 1 [kg]	11950
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	8800
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	110,00
Hump	H2
Valve protection	VS V
Single / multi-part	einteilig
Rim material	steel

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



RAL	RAL1004
Cavity Sealed	No
Forest reinforcement	flange reinforcement Ø16 mm
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	12
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	372
Bolt hole circle diameter [mm]	425
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No