

RIMS

Product groupRimsItem number33060826Valid rim sizeAG 24.00 x 30.5 H2Rim connection10/281/335Bolt hole designA3Offset (mm)-50Rim colourSilverBrandJantsa		
Valid rim size Rim connection 10/281/335 Bolt hole design A3 Offset (mm) -50 Rim colour Silver	Product group	Rims
Rim connection 10/281/335 Bolt hole design A3 Offset (mm) -50 Rim colour Silver	Item number	33060826
Bolt hole design A3 Offset (mm) -50 Rim colour Silver	Valid rim size	AG 24.00 x 30.5 H2
Offset (mm) -50 Rim colour Silver	Rim connection	10/281/335
Rim colour Silver	Bolt hole design	A3
	Offset (mm)	-50
Brand Jantsa	Rim colour	Silver
	Brand	Jantsa





Technical Informations	
Load capacity of rim 1 [kg]	11800
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	8700
Speed Rims 2 [km/h]	65
Load capacity of rim 3 [kg]	13750
Speed Rims 3 [km/h]	25
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	115,00
Hump	H2
Valve protection	VS H

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No