

## **RIMS**

Product group	Rims
Item number	33060880
Valid rim size	10.00 - 24 / 2.0
Rim connection	12/371/425
Bolt hole design	M22
Offset (mm)	+30
Rim colour	Black
Brand	Jantsa





Technical Informations	
Load capacity of rim 1 [kg]	12500
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	10750
Speed Rims 2 [km/h]	30
Maximum speed [km/h].	30
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	75,00
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	six-part
Rim material	steel

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



RAL	RAL9005
Cavity Sealed	No
Rim design industry	Standard
Disc thickness [mm]	16.0
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	НВ
Number of bolt holes	12
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	371
Bolt hole circle diameter [mm]	425
Valve seat	External Valve
Preassembled valve	No