

## **RIMS**

Product group	Rims
Item number	33060901
Valid rim size	11.25 - 25 / 1.7
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+80
Rim colour	Grey
Brand	Jantsa



## **Technical Informations** Load capacity of rim 1 [kg] 7300 Speed Rims 1 [km/h] 70 70 Maximum speed [km/h]. Type of drive Angetriebene & gezogene Achse Nettogewicht [kg] (gültig) 75,00 Hump kein Hump Single / multi-part mehrteilig Quantity multi-piece five-part Rim material steel RAL7021 **RAL Cavity Sealed** No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rim design industry	Standard
Disc thickness [mm]	15
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Preassembled valve	No