Bohnenkamp Moving Professionals

13.11.2024

RIMS

Product group	Rims
Item number	39122090
Valid rim size	8.50 L x 12 H2
Rim connection	6/90/120
Bolt hole design	M12
Offset (mm)	-33
Brand	Hartwig



Technical Informations

Load capacity of rim 1 [kg]	1000
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Nettogewicht [kg] (gültig)	8,80
Hump	H2
Single / multi-part	einteilig
Rim material	steel
Rim colour (manufacturer's designation)	Kubota - orange
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

13.11.2024

Rim centering	НВ
Number of bolt holes	6
Bolt hole diameter [mm]	15.5
hub hole diameter [mm].	90
Bolt hole circle diameter [mm]	120
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.