

RIMS

Product group	Rims
Item number	39122320
Valid rim size	W 10 x 52
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+145
Rim colour	Red
Brand	Hartwig





Technical Informations

Load capacity of rim 1 [kg]	4600
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Nettogewicht [kg] (gültig)	192.00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL3000
Cavity Sealed	Yes
Disc thickness [mm]	11
Verschweißung beidseitig	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Preassembled valve	No