

RIMS

Product group	Rims
Item number	39122921
Valid rim size	15 x 30
Rim connection	8/170/220
Bolt hole design	D23
Offset (mm)	+23
Rim colour	Silver
Brand	Levypyoera



Technical Informations

Load capacity of rim 1 [kg]	13812
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	12154
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	80,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
Surface treatment	SB

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	НВ
Number of bolt holes	8
Bolt hole diameter [mm]	23
Countersinking	Cone
Countersinking of the cone [°].	C80
hub hole diameter [mm].	170
Bolt hole circle diameter [mm]	220
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No