Bohnenkamp Moving Professionals

22.09.2024

RIMS

Product group	Rims
Item number	39123010
Valid rim size	W 10 x 52
Rim connection	10/281/335
Bolt hole design	В3
Offset (mm)	+105
Rim colour	Red
Brand	Levypyoera



Technical Informations

Load capacity of rim 1 [kg]	4400
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	193.00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
Surface treatment	SB

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

RAL	RAL3000
Cavity Sealed	No
Disc thickness [mm]	15
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No