

RIMS

Product group	Rims
Item number	39123051
Valid rim size	W 15 x 50
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+100
Rim colour	Silver
Brand	Levvyoera



Technical Informations

Load capacity of rim 1 [kg]	8455
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7441
Speed Rims 2 [km/h]	65
Load capacity of rim 3 [kg]	11753
Speed Rims 3 [km/h]	10
Load capacity of rim 4 [kg]	9893
Speed of wheels 4 [km/h].	25
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	190,00

Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
Surface treatment	SB
RAL	RAL9006
Colour type	Glossy
Cavity Sealed	No
Disc thickness [mm]	15
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No