

RIMS

Product group	Rims
Item number	39123066
Valid rim size	W 12 x 50
Rim connection	10/281/335
Bolt hole design	B3
Rim colour	Silver
Brand	Trinker





Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	50
Maximum speed [km/h].	50
Nettogewicht [kg] (gültig)	179,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	15
Verschweißung beidseitig	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Preassembled valve	No