Bohnenkamp Moving Professionals

22.09.2024

RIMS

Product group	Rims
Item number	39123068
Valid rim size	DW 16 x 46
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+6
Rim colour	Red
Brand	Levypyoera



Technical Informations

Load capacity of rim 1 [kg]	5129
Speed Rims 1 [km/h]	65
Load capacity of rim 2 [kg]	4514
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	188,80
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL3000

Bohnenkamp Moving Professionals

Cavity Sealed	No
Disc thickness [mm]	15
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No

22.09.2024