

RIMS

Product group	Rims
Item number	39123122
Valid rim size	W 15 L x 50
Rim connection	12/350/400
Bolt hole design	M20
Offset (mm)	+35
Rim colour	Silver
Brand	Levypyoera



Technical Informations

Load capacity of rim 1 [kg]	6770
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Nettogewicht [kg] (gültig)	214,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	15
Verschweißung beidseitig	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Ventilation holes	No
Rim centering	НВ
Number of bolt holes	12
Bolt hole design EUWA	M20
Bolt hole diameter [mm]	24
hub hole diameter [mm].	350
Bolt hole circle diameter [mm]	400
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No