

RIMS

| | |
|------------------|--------------|
| Product group | Rims |
| Item number | 39123162 |
| Valid rim size | DW 25 B x 26 |
| Rim connection | 12/371/425 |
| Bolt hole design | A3 |
| Offset (mm) | -70 |
| Rim colour | Anthrazit |
| Brand | Levvyoera |



Technical Informations

| | |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 7780 |
| Speed Rims 1 [km/h] | 65 |
| Maximum speed [km/h]. | 65 |
| Type of drive | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig) | 99,00 |
| Hump | kein Hump |
| Valve protection | VSH |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL7016 |
| Cavity Sealed | No |

| | |
|---------------------------------------|----------------|
| Disc thickness [mm] | 15 |
| Verschweißung beidseitig | No |
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 12 |
| Bolt hole design EUWA | B22 ES 36 |
| Bolt hole diameter [mm] | 27 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| hub hole diameter [mm]. | 371 |
| Bolt hole circle diameter [mm] | 425 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |